

## 3-D Image Warping

IBMRL

Copyright © Manuel M. Oliveira

## 3-D Image Warping [McMillan - Bishop 95]


- Maps images with depth onto arbitrary image planes
- Scene geometry implicitly represented by a pinhole camera and per pixel depth

Demo

IBMRL

Copyright © Manuel M. Oliveira

## 3-D Image Warping [McMillan - Bishop 95]




IBMRL

Copyright © Manuel M. Oliveira

## 3-D Image Warping (Cont.)

- What we need to know
  - Camera parameters
    - Position ( $C_s$ )
    - Orientation, focal distance, horizontal and vertical FOVs ( $M_s$ )
  - Per pixel depth ( $t_s$ )




IBMRL

Copyright © Manuel M. Oliveira

## 3-D Image Warping (Cont.)

- Produces correct 3-D reprojections from arbitrary views
- Compute the projections onto arbitrary image planes by solving



IBMRL

Copyright © Manuel M. Oliveira

## 3-D Warping Equation

$$\dot{C}_t + t_t M_t p_t = \dot{C}_s + t_s M_s p_s$$

$$p_t \doteq M_t^{-1} ((\dot{C}_s - \dot{C}_t) + t_s M_s p_s)$$

$$p_t \doteq \underbrace{M_t^{-1} (\dot{C}_s - \dot{C}_t)}_{\text{epipole}} + \underbrace{M_t^{-1} M_s p_s}_{\text{planar perspectiveproj}}$$

- $\delta_s = 1/t_s$  is called the *generalized disparity* of pixel  $p_s$
- 3-D image warping is equivalent to a texture mapping operation followed by a per pixel shift proportional to  $\delta_s$  in the direction of the epipole
- Generalizes conventional texture mapping

IBMRL

Copyright © Manuel M. Oliveira

## 3-D Warping Equation (Cont.)

$$p_t \doteq \underbrace{M_t^{-1}(\dot{C}_s - \dot{C}_t)}_{\text{epipole}} \delta_s + \underbrace{M_t^{-1} M_s P_s}_{\text{planar perspectiveproj}}$$

$$\alpha \begin{bmatrix} u_t \\ v_t \\ 1 \end{bmatrix} = \begin{bmatrix} \tilde{a}_t & \tilde{b}_t & \tilde{c}_t \end{bmatrix}^{-1} (\dot{C}_s - \dot{C}_t) \delta_s(u_s, v_s) + \begin{bmatrix} \tilde{a}_t & \tilde{b}_t & \tilde{c}_t \end{bmatrix}^{-1} \begin{bmatrix} \tilde{a}_s & \tilde{b}_s & \tilde{c}_s \end{bmatrix} \begin{bmatrix} u_s \\ v_s \\ 1 \end{bmatrix}$$

$$\alpha \begin{bmatrix} u_t \\ v_t \\ 1 \end{bmatrix} = \begin{bmatrix} \tilde{a}_t & \tilde{b}_t & \tilde{c}_t \end{bmatrix}^{-1} \begin{bmatrix} \tilde{a}_s & \tilde{b}_s & \tilde{c}_s & (\dot{C}_s - \dot{C}_t) \end{bmatrix} \begin{bmatrix} u_s \\ v_s \\ 1 \\ \delta(u_s, v_s) \end{bmatrix}$$

IBMRL

Copyright © Manuel M. Oliveira

## 3-D Warping Equation (Cont.)

$$u_t = \frac{\tilde{a}_s \cdot (\tilde{b}_t \times \tilde{c}_t) u_s + \tilde{b}_s \cdot (\tilde{b}_t \times \tilde{c}_t) v_s + \tilde{c}_s \cdot (\tilde{b}_t \times \tilde{c}_t) + (\dot{C}_s - \dot{C}_t) \cdot (\tilde{b}_t \times \tilde{c}_t) \delta(u_s, v_s)}{\tilde{a}_s \cdot (\tilde{a}_t \times \tilde{b}_t) u_s + \tilde{b}_s \cdot (\tilde{a}_t \times \tilde{b}_t) v_s + \tilde{c}_s \cdot (\tilde{a}_t \times \tilde{b}_t) + (\dot{C}_s - \dot{C}_t) \cdot (\tilde{a}_t \times \tilde{b}_t) \delta(u_s, v_s)}$$

$$v_t = \frac{\tilde{a}_s \cdot (\tilde{c}_t \times \tilde{a}_t) u_s + \tilde{b}_s \cdot (\tilde{c}_t \times \tilde{a}_t) v_s + \tilde{c}_s \cdot (\tilde{c}_t \times \tilde{a}_t) + (\dot{C}_s - \dot{C}_t) \cdot (\tilde{c}_t \times \tilde{a}_t) \delta(u_s, v_s)}{\tilde{a}_s \cdot (\tilde{a}_t \times \tilde{b}_t) u_s + \tilde{b}_s \cdot (\tilde{a}_t \times \tilde{b}_t) v_s + \tilde{c}_s \cdot (\tilde{a}_t \times \tilde{b}_t) + (\dot{C}_s - \dot{C}_t) \cdot (\tilde{a}_t \times \tilde{b}_t) \delta(u_s, v_s)}$$

$$r = w_{11}u_s + w_{12}v_s + w_{13} + w_{14}\delta(u_s, v_s)$$

$$s = w_{21}u_s + w_{22}v_s + w_{23} + w_{24}\delta(u_s, v_s)$$

$$t = w_{31}u_s + w_{32}v_s + w_{33} + w_{34}\delta(u_s, v_s)$$

$w_i$  recomputed as the target camera parameters change

Sub-expressions of  $r$ ,  $s$  and  $t$  can be updated incrementally


$$u_t = \frac{r}{t}, \quad v_t = \frac{s}{t}$$

IBMRL

Copyright © Manuel M. Oliveira

## Disocclusion Artifacts

- Exposures of areas not visible in the original image introduce artifacts
- Need samples from other images to fill the holes




IBMRL

Copyright © Manuel M. Oliveira

## Occlusion-Compatible Order

- List priority algorithm for solving visibility




IBMRL

Copyright © Manuel M. Oliveira

## Occlusion-Compatible Order (Cont.)


**Epipole:** projection one center of projection onto the image plane of the other camera



IBMRL

Copyright © Manuel M. Oliveira


## Occlusion-Compatible Order



IBMRL

Copyright © Manuel M. Oliveira

## Occlusion-Compatible Order (Cont.)



IBMRL

Copyright © Manuel M. Oliveira

## Occlusion-Compatible Order (Cont.)

### Algorithm summary

- Find the project. of target COP onto the source image plane (epipole)
- Divide source image plane into at most 4 sheets based on the epipole
- If *target COP* is behind *source COP*
  - for each sheet
    - warp samples from the epipole towards the borders of the sheet
  - else
    - for each sheet
      - warp samples from the borders of the sheet towards the epipole

IBMRL

Copyright © Manuel M. Oliveira

## Computing the Epipole

- Projecting  $C_t$  onto the source image plane

$$\begin{bmatrix} e_x \\ e_y \\ e_z \end{bmatrix} = M_s^{-1}(\dot{C}_t - \dot{C}_s)$$

- The coordinates of the projected point are given by


$$\vec{e} = \begin{bmatrix} e_x / e_z \\ e_y / e_z \end{bmatrix}$$

IBMRL

Copyright © Manuel M. Oliveira

## Splitting the Source Image

- The epipole splits the source image in at most 4 sheets




IBMRL

Copyright © Manuel M. Oliveira

## Warping Direction

- $e_z$  negative: target COP behind source COP




IBMRL

Copyright © Manuel M. Oliveira

## Warping Direction

- $e_z$  non-negative: target COP aligned with or in front of the source COP



IBMRL

Copyright © Manuel M. Oliveira

## Warping Images from Real Environments [UNC Chapel Hill]



Reading room: courtesy of the UNC Chapel Hill Image-Based Rendering Group

IBMRL

Copyright © Manuel M. Oliveira

IBMRL

Copyright © Manuel M. Oliveira

## Depth Acquisition



- Movable cart containing the necessary hardware to acquire range data: rangefinder and panning motor, computer display and B/W monitor (for showing the laser position), PC and battery
- Problems with specular and black surfaces


Courtesy of Lars Nyland, UNC Chapel Hill

IBMRL

Copyright © Manuel M. Oliveira

## Rangefinder and Panning Motor

- The rangefinder, scanning mirror, and pan-tilt unit. The hi-ball tracking unit is on top, with 6 lenses looking at the ceiling




Courtesy of Lars Nyland, UNC Chapel Hill

IBMRL

Copyright © Manuel M. Oliveira

## Range Maps

- Examples



IBMRL

Copyright © Manuel M. Oliveira

## Range Maps (Cont.)

- Warped range map using Multiple-Center-of-Projection Images [Rademacher 98]



Courtesy of Paul Rademacher and Lars Nyland, UNC Chapel Hill

IBMRL

Copyright © Manuel M. Oliveira

## Color Images



- After an environment is scanned, the laser is removed from the panning unit and replaced with the camera
- Camera with mounting bracket to position the COP of the lens at the approximate location as the COP of the rangefinder



Images courtesy of Lars Nyland, UNC Chapel Hill

IBMRL

Copyright © Manuel M. Oliveira

## Color Images (Cont.)

- In order to minimize lens distortions, several overlapping images are taken and only the central portions of the images are used



Courtesy of Lars Nyland,  
UNC Chapel Hill

IBMRL

Copyright © Manuel M. Oliveira